

Technical Specifications

KEY HIGHLIGHTS







GENERAL DESIGN	
MATERIAL	Anti-corrosive steel
SIZE	(HxWxD) 65.90" x 18.70" x 14.92"
WEIGHT	198.42 lb
TEMPERATURE/HUMIDITY	-13°F to +131°F / up to 95% relative humidity at 131°F
COLOR	Sterling Grey, Titanium Grey, Moss Green, Magic Blue, or Jet Black
COMPLIANCE	EN 12414 / CE marking
USER INTERFACE	
DISPLAY	 9.7" full-color touch screen monitor with LED back lighting 262,144 colors Monitor dimensions: 8.75" x 5.75"; Monitor resolution: 1024 x 768 pixels
PAYMENT OPTIONS	
COIN SELECTOR	 Patented motor-driven coin selector: Max. 14 types of coins or tokens (programmable) Automatic opening upon coin insertion Multi-criteria coins identification
BANK NOTE ACCEPTOR	Cashcode SM/MSM backload validator4-way acceptance
CONTACT & CONTACTLESS	Smartcards & bank cards, EMV 2000, PCI-PED, UKCC, Mifare®, ISO 14443, NFC
OTHER	Cashless configuration available
COLLECTION (2 Patented Methods Available)	 Transfer: Fixed cashbox with removable canister: 3.31 lb empty; approx. 48.5lb full/5.81 Rapide: Exchangeable cashbox: 3.53 lb empty; approx. 43.21 lb full / 4.61 Bank Note Acceptor (optional) - separate exchangeable cashbox & stacker Coins: 6.03 lb empty; approx 24.91 lb full of 2,000 quarters / 3.51 Bill stacker: 1,000 bills
POWER SUPPLY	Solar or Mains
SECURITY	 Money storage EN 14450 Level 2 certified Attack detection Additional shieldings and security enhancements
TICKET	 Thermal graphic printer: Horizontal or vertical printing, Text and logo, 203 dots per inch per line, 448 dots per column Paper or self-adhesive tickets Without BNA option: standard format (w x I) 2.36" x 2.75" - cap. up to 6,500 tickets With BNA option: 4" minimum length - capacity up to 4,500 tickets
COMMUNICATIONS	4G modem, Ethernet
ENVIRONMENT	More than 95% recyclable (ISO 22628) / European directives - RoHS and WEEE